

IllumiSign™ Solar LED Sign & Billboard Lighting

The better, brighter floodlight

FEATURES

Max Lite™ reflector maximizes LED light output.

Solar powered illumination eliminates connection hassles.

Maintenance free, vandal-resistant construction.

10 days autonomy (battery reserve).

Installs quickly and easily.

SPECIFICATIONS

6 hr, 8hr, and dusk to dawn run times.

For complete information, please consult individual specification sheets for the various components including the IllumiSign 1, 2 and 3 Quad floodlight fixtures, battery enclosure, gel cell battery, SOL EternO® controller and power connectors.

Solar panel specifications may vary by manufacturer.

* Contact us for exact system requirements.



Billboard Size Height x Length	Example Location*	Fixture(s)	Example Run time* (hrs)	Solar System		Panel Dimensions Length x Width (inches)	Panel Power (Output Amps) (amps@12v)	System Weight (pounds)
				Panel Size	Batteries (amp hrs req'd)			
10' x 20' 12' x 24'	Chicago, IL	1	6	240 watts (3 x 80)	200	46.75 x 62.40	13.65	240
12' x 30' 12' x 36'	Nashville, TN	2	6	320 watts (4 x 80)	300	46.75 x 83.20	18.20	450
14' x 48'	Los Angeles, CA	3	6	369 watts (3 x 123)	400	59.02 x 78.18	21.48	440

Fixture	Dimensions Length x Width (inches)	EPA @ 45 degrees (Effective Projected Area)	Weight (pounds)
Sol 3Q LED Floodlight	19 x 5.5	0.73 sq. ft.	8 lbs.



Reliable. Renewable. Remarkable.



www.ecogise.co.nz