

IllumiSign™ Transit Shelter Advertising Lighting

The better brighter light bar for shelter signs

FEATURES

- Modular design
- Plug in components
- Uniform illumination with no hot spots
- Low maintenance light source compared to fluorescent
- Built to endure with superior reliability
- Easy to instal or relocate
- Exclusive solar option
- 5-year warranty
- National Electric Code Article 690 compliant

SPECIFICATIONS

System voltage	12V DC
Solar system panel*	80 to 246 watts
Batteries	12V 100AH gel cell maintenance-free
Battery reserve	5 day autonomy
Light color temperature	6500 K
Lightsource	Sol's LED Uni-light
LED life span	100,000 hours
Operating temperature	-20 F to +120 F
Storage temperature	-40 F to +180 F
Operating humidity, non-condensing	100%
Storage humidity, non-condensing	100%
Operating hours	Programable, 6 hrs to dusk to dawn
Dimensions, L (including mounting) x H x D	45.1" x 2" x 2" (back-to-back) 69" x 2" x 2" (V-box)
Enclosure	Aluminum
Weight	3.5 Lbs

*Solar panel specifications may vary by manufacturer and system size will vary with location.



Reliable. Renewable. Remarkable.



22 Quarantine Road, Annesbrook
 PO Box 1373 | Nelson 7040 | New Zealand
 Ph: 0800 4 326 4473 | Fx: 03 547 1324
www.ecogise.co.nz